

A glowing orb, possibly a moon or planet, is positioned at the top center of the frame against a dark, gradient sky. Below it, a wooden deck is shown from a low-angle perspective, receding towards a bright light source on the horizon, creating a silhouette effect. The deck's surface is the primary focus, with the brand name printed on it.

Even we didn't think it could be done.

PWT
TREATED™
TREATED RIGHT™

The world's first manufacturer-treated LVL and the dawn of a new era in engineered decking solutions
Protects against fungal rot, decay and insects, and has a 25-year warranty,* 50-year life expectancy
No-gradient, uniformly treated, 2X PTI retentions required for UC3B
And, of course, all of the advantages of PWT LVL

Find out more at pacificwoodtech.com/treated

PACIFIC™
WOODTECH

*Excludes industrial applications, such as scaffold plank and concrete forming.



Product Highlights

- PWT is excited to add a one-of-a-kind innovative product to our portfolio.
- PWT Treated LVL will roll out this fall as the only manufacturer-treated LVL and will include a 25-year limited, transferable warranty.*
- PWT Treated LVL is protected against damage caused by fungal rot, decay and wood-destroying insects, including Formosan termites (interior or exterior usage).
- We use a proprietary treatment system and process, utilizing TRU-CORE® technology.

The Product

- PWT Treated LVL can be used in severe above-ground UC3B applications requiring UC4A treatment retentions per AWPA, including severe, critical and hard-to-replace above-ground uses, such as:
 - Deck substructures, exterior columns and sill plates.
- Treatment is added during the LVL manufacturing process, which fully penetrates throughout each veneer layer, offering complete protection from the inside out.
- No treatment gradient – and double (2X) the preservative retention required in various standards around the world.
- Additionally, envelope treated for best surface properties.
- No added VOCs.

Grade (no strength reduction after treatment)

2.0E_{True}, 2800 F_b

Beam Sizes

3½" x	5½"	7¼"	9½"	11⅝"	14"	16"	18"
5¼" x	5½"	7¼"	9½"	11⅝"	14"	16"	18"
7" x	beams would be assembled in the field from 3½" LVL (generally small volume)						

Column Sizes

3½" x	3½"	5½"	7¼"
5¼" x	-	5½"	7¼"


PWT will be introducing and supplying other treated sizes and products, such as:

- 1½ and 1¾ for framing and joist applications.
- Treated scaffold plank.

* Excludes industrial applications, such as scaffold plank and concrete forming.

Product Identification

- Product will have a muted olive tint
- Stamp: "PWT TREATED"
- Special PWT Treated LVL paper wrap



1850 Park Lane | Burlington, WA 98233
 TF 888.707.2285 | O 360.707.2200 | F 360.395.7003

www.pacificwoodtech.com